



Air Conditioning Systems

Up to **13.3 CEER**

# Window Air Conditioner



### Quick & Easy Installation

Includes a quick-snap bracket, and can be installed in 3 simple steps.



### Ultra Quiet

The U-shaped design blocks the noise coming from the compressor outside.



### Long-distance Airflow up to 20 feet

The strong airflow allows you to feel the cold air up to 20 feet away.

**Quiet**

**Smart**

**Efficient**

**5 YEARS**  
COMPRESOR  
**1 YEAR**  
PARTS  
**WARRANTY**



**Model:** MWAUQB-12HRFN8-BCL0

115V Applications

Consult your Air Conditioning professional for more details.

See reverse for product information.

**OLDACH**

REFRIGERATION, AIR CONDITIONING & VENTILATION SUPPLIER

[www.oldachpr.com](http://www.oldachpr.com)

		Indoor	MWAUQB-12HRFN8-BCL0
Power supply		V-Ph-Hz	115V,1Ph,60Hz
Cooling	Capacity	Btu/h	12000
	CEER	Btu/h/W	13.3
	Input	W	1214
	Current	A	12.0
	Standby power	W	1.4
Rated Power Input		W	1250
Rated Current c		A	13.8
Compressor	Capacity	W	2770
	Input	W	725 ±3%
	current	A	5.0
	Refrigerant oil/oil charge	ml	ESTER OIL VG74 240±10
Refrigerant type		Type	R32
Design pressure(145psi=1MPa )(L/H)			0.45kg
		psi	300/520
Fan Motor	Speed(hi/mi/lo)	r/min	2000/1540/1310
	Insulation class		B
Evaporator	a.Number of rows		3
	b.Tube pitch(a)x row pitch(b)	mm	21x13.37
	c.Fin spacing	mm	1.2
	d.Fin type (code)		Hydrophilic aluminum
	e.Tube outside dia.and type	mm	Φ7,Inner groove tube
	f.Coil length x height x width	mm	365x273x26.74
	g.Number of circuits		2
Indoor side air flow(Hi/Mi/Lo)		m3/h	520/390/320
		ft3/min	305.88/229.41/188.24
Indoor side noise level (Hi/Mi/Lo)		dB(A)	58/53/45
			1 m3/h = 0.588 ft3/min
Condenser	a.Number of rows		3
	b.Tube pitch(a)x row pitch(b)	mm	21x13.37
	c.Fin spacing	mm	1.3
	d.Fin type (code)		Hydrophilic aluminum
	e.Tube outside dia.and type	mm	Φ7,Inner groove tube
	f.Coil length x height x width	mm	395x331.5x40.11
	g.Number of circuits		2
Outdoor air flow (Hi/Med/Lo) m3/h		m3/h	770/-/-
1 m3/h = 0.588 ft3/min		ft3/min	452.94////
Outdoor side noise level(Hi)		dB(A)	69/-/-
Power cord type			14#x3
Power Cord Length		mm	1980
Power Cord Length		ft	6.50
Control type			(Remote Control)
Operation temp	indoor(cooling/heating)	°C	17-32/0-27
	outdoor(cooling/heating)	°C	18-43//
Dimension(W*D*H)		mm	493x563x353
		in	19.41x22.17x13.90
Packing (W*D*H)		in	21.34x24.76x16.30
Net/Gross weight		lb	57.98/66.25
Loading quantity 20' /40' /40'HQ		Pieces	185/395/474
Window Opening	Width(Min/Max)(Inches)	in	24/38.5
	Height(Min)(Inches)	in	14.5