

Portable Units Air Conditioners



EasyCool • Easy Operation • Easy Installation

Model
MPPTB-12RN8-BCG8
12,000 BTU

Easy and safe installation accessories included.
115v Applications.

See reverse for product information.



OLDACH
REFRIGERATION, AIR CONDITIONING & VENTILATION SUPPLIER

		Model MPPTB-12RN8-BCG8	
Power supply		V-Ph-Hz	115V_1Ph,FREQUENCY_60HZ
Cooling	Capacity	Btu/hr	12000
	Input	W	1200
	Current	A	11.8
	EER	W/W	2.93
Rated Power Input		W	1250
Rated Current		A	12
Compresor	Capacity	W	2035/3255
	Input	W	325/826
	Rated current(RLA)	A	2.40/5.65
	Refrigerant oil	ml	ESTER OIL VG74 310
Fan Motor	Speed(hi/mi/lo)	r/min	1300/940/760
Indoor Side Motor	Input	W	36
	Speed(hi/mi/lo)	r/min	1300/940/760
	Insulation class		E
Evaporator	a.Number of rows		2
	b.Tube pitch(a)x row pitch(b)	mm	21x13.37
	c.Fin spacing	mm	1.3
	d.Fin type (code)		Hydrophilic aluminum
	e.Tube outside dia.and type	mm	Φ7Inner groove tube
	f.Coil length x height x width	mm	370*378*26.74
	g.Number of circuits		2
Indoor side air flow (Hi/Mi/Lo)		m3/h	639/435/338
Indoor side noise level(Hi/Mi/Lo)		dB(A)	53.5/49.5/42.5
Condenser	a.Number of rows		4
	b.Tube pitch(a)x row pitch(b)	mm	14.5x12.56
	c.Fin spacing	mm	1.2
	d.Fin type (code)		Unhydrophilic aluminium
	e.Tube outside dia.and type	mm	Φ5Inner groove tube
	f.Coil length x height x width	mm	320*331.5*46.4
	g.Number of circuits		2
Outdoor side noise level (Hi)		dB(A)	0
Refrigerant type			R32/0.40kg
Plug type			LCDI(5-15P)
Power cord length		mm	1700
Control type			Remote Control
Operation temp (room temp.)		°C	17-35
Dimension (W*D*H)		inch	19.53x16.73x32.48
Packing (W*D*H)		inch	22.24x18.07x34.35
Net/Gross weight		lbs	72.75/81.57